



## Shibaura Machine

View the Future with You

### ISO 9001



GOTEMBA plant

#### SHIBAURA MACHINE CO., LTD.

**TOKYO MAIN BRANCH**  
2-2, Uchisaiwaicho 2-Chome, Chiyoda-ku, Tokyo 100-8503, Japan  
TEL:+81-3-3509-0271 FAX:+81-3-3509-0335

**SHIBAURA MACHINE CO., AMERICA**  
Chicago Head Office  
755 Greenleaf Avenue, Elk Grove Village, IL 60007, U.S.A.  
TEL:847-709-7199 FAX:847-593-9741

**Canada Branch**  
6 Shields Court, Suite 101, Markham, Ontario L3R 4S1, CANADA  
TEL:905-479-9111 FAX:905-479-8339

**SHIBAURA MACHINE UK LTD.**  
66 Burners Lane, Kiln Farm, Milton Keynes MK11 3HD  
UNITED KINGDOM  
TEL:+44-(0)1908-562327 FAX:+44-(0)1908-562348

**SHIBAURA MACHINE SINGAPORE PTE. LTD.**  
Head Office  
123 Pioneer Road, Singapore 639596, SINGAPORE  
TEL:68611455 FAX:68612023

**TOSHIBA MACHINE [THAILAND] CO., LTD.**  
127/28 Panjathanee Tower, 23rd Floor, Nonthree Road, Khwaeng Chong  
Nonthree, Khet Yannawa, Bangkok 10120, THAILAND  
TEL:02-681-0158 FAX:02-681-0162

**TOSHIBA MACHINE [VIETNAM] CO., LTD.**  
2nd, VIT Tower, No.519, Kim Ma Street,  
Ba Dinh District, Hanoi, VIETNAM  
TEL:024-2220-8700,8701 FAX:024-2220-8702

**TOSHIBA MACHINE (CHENNAI) PRIVATE LIMITED**  
No. 65 (P.O. Box No. 5), Chennai-Bangalore Highway, Chembarambakkam,  
Poonamallee Taluk, Thiruvallur, Chennai-600123, Tamil Nadu, INDIA  
TEL:044-2681-2000 FAX:044-2681-0303

**SHIBAURA MACHINE TAIWAN CO., LTD.**  
No.62, Lane 188, Jui-Kuang Road, Nei-Hu District, Taipei, TAIWAN  
TEL:02-2659-6558 FAX:02-2659-6381

**SHANGHAI TOSHIBA MACHINE CO., LTD.**  
Head Office  
4788, Jin Du Road, Xinzhuang Industry Zone, Shanghai, 201108  
PEOPLE'S REPUBLIC OF CHINA  
TEL:021-5442-0606 FAX:021-5866-2450

\* We reserve the right to change any of specifications in this catalog without notice in order to effect improvements.



**SHIBAURA MACHINE's best-selling TUE**  
**TUE series is the economical solution for your**  
**turning capabilities.**

**Optional (S) type has a live spindle that performs**

# TUE-Series

## High accuracy

- Extremely rigid anti-friction pre-loaded linear roller guide used on the X-axis slide unit for high speed and accurate positioning.
- Ram travel (Z-axis) is guided by heavy duty box way.
- Gear box is apart from bed and thermal displacement is smaller.
- High accurate table index by Cs axis control.

## High efficiency

- All main components are made by high quality cast iron. Column structure is rigid box type.
- Maximum table speeds are increased. (TUE-150 400min<sup>-1</sup>, TUE-200 240min<sup>-1</sup>)
- Live Spindle employed built in motor(18.5/15kW / 25/20HP). Gearless drive assures high efficient milling capability. (TUE-150(S), TUE-200(S))

## Automatic function

- Automatic Tool Changer (ATC) (Option)
- Automatic diameter and step difference measuring device, Automatic tool tip measuring device. (Both are option)

Main specifications		TUE-150	TUE-200
Table diameter	mm(in)	1450(57.09)	2000(78.74)
Maximum swing	mm(in)	2000(78.74)	2400(94.09)
Maximum cutting height	mm(in)	1550(67.72)	
Maximum table load	kg(lb)	8000(17600)	15000(33070)
Vertical travel of ram	mm(in)	900(35.43)	
Table speeds	min <sup>-1</sup>	2-400 (Low : 2~100 High : 8~400)	2-240 (Low : 2~60 High : 8~240)
Table drive motor	kW(HP)	45 / 37(60 / 50)	

**series has been enhanced.**  
**turning needs yet achieves high quality**




**drilling and tapping and boring operations.**



CNC FANUC Series 0i-TF


## Rigidity and accuracy of main components of our TUE series are the essence of high quality.

Robust and high quality cast iron components of TUE series assures high rigidity and accuracy of the machine.




### Wall type column

The extended width of the crossrail support side, delivers robust and strong combination, including a larger column cross section in comparison to previous TUE model.



### One-body cross rail

Rigidity of one-body construction goes up 50% higher than previous TUE model.




Cutting force which are absorbed by the ram are transferred efficiently through a one-body crossrail and "unique" wall type column design that extends to the center of the table. This structure assures high rigidity and high accuracy of the machine.

The table supported by two bearings assures stable and high-speed powerful cutting even when machining a large diameter workpiece.




### Maximum load on table




\* Machine limitation:  
Depends on the size and shape of the workpiece.

### Table torque (TUE-150)



### Table torque (TUE-200)



T-slots incorporated on the table top, are used to guide four independent manually-operated jaws and to clamp a workpiece.


The bed made of cast iron has rationally arranged ribs for rigid table support. The rear side of the bed is connected with column and contain a main gear drive system.





## Rail head for improved machine performance

The rail head is positioned horizontally (X-axis) and the ram vertically (Z-axis) by means of large-diameter ball screws of which each is supported by special angular contact ball bearings. The X-axis slideways consists of linear rolling guides and the Z-axis slideway is composed of non-metallic liners to assure high positioning accuracy, high axis feed and heavy-duty operations.




TUE-(S) type machine equipped with a live spindle reduces the amount of setups, in order to achieve a more efficient process.




Tool can be clamped/unclamped automatically in the spindle (ISO taper No.50) with the collet type pull stud and the spindle is driven by the AC type motor located at the top of the ram.

## Live Spindle torque diagram



## Cutting force diagram (Turning)



## Standard accessories

- (1) Installation parts 1 set
- (2) Special service tools 1 set
- (3) Automatic slideway lubricating unit 1 set
- (4) Crossrail elevating device 1 set
- (5) Four (4) independent manually-operated jaws 1 set
- (6) Steel telescopic crossrail slide cover 1 set
- (7) Splash cover 1 set  
(Height between table-top to cover top: 1775 mm [69.9 inch])

## Turning basic package

- (1) Automatic tool changer (ATC)  
Tool storage capacity : 18 tools (6 tools for turning, 12 tools for milling)  
Total tool weight : 360kg [794 lb]  
Tool changing time (\*Note 1) 30sec Note 1 : Tool-to-tool time.  
Type of tool shank for turning : 7/24 taper No.50 and flange (double face contact type) for milling 7/24 taper No.50 (\*Note 1)  
Type of pull stud : 50PU (1-8UNC) (JIS B 6339-1992)  
Maximum tool size : 400W×150T×500L mm [15.7W×5.9T×19.7L inch]  
Maximum tool weight : 50 kg (110 lb)  
Method of tool selection : Soft tool pot address
- (2) Work light (LED) : 10 W
- (3) Operator call lamp  
This lamp is mounted on top of the arm right side.  
Green : Illuminated during automatic operation.  
Yellow : Illuminated when M00, M01, M02, M30 or M52 has been executed.  
Red : Illuminated at NC alarm or machine alarm generation.

- (4) Table lubricant oil cooling unit
- (5) Automatic power OFF
- (6) Chip conveyor with tank / coolant unit  
Used to discharge chips recovered by the chip scraper from the machine.  
Not available to operate by inputting M-code (only manual push button).  
Coolant tank capacity : 400 L [105.7 gal]  
Standard type : Motor : AC 4P, 0.2kW [0.27 HP]
- (7) Chip scraper  
Used to discharge chips from around the table.  
Available to operate by inputting M-code and manual push button.  
Drive motor : AC 4P, 0.4 kW [0.54 HP]
- (8) Additional table center hole and tap hole  
Table center hole for fixture : Dia. 100 mm [3.94"]  
Tap size : M24×pitch 3.0

## User Option

- (9) High type column+300mm [11.81"]
- (10) Long type ram+350mm [13.78"]
- (11) Dia. 1600 mm [63"] table specification (for TUE-150)  
Maximum rotating speed is limited to 320 min<sup>-1</sup>.
- (12) High type independent manually-operated jaw set (4 pieces)
- (13) Separate type independent manually-operated Soft jaw set (4 pieces)
- (14) Separate type independent manually-operated Hard jaw set (4 pieces)
- (15) Special stroke type independent manually-operated jaws set (4 pieces)  
Jaw stroke : 100 mm [3.94"]
- (16) Tool holder (see below)
- (17) X-axis linear scale feedback
- (18) Automatic radius and step difference measuring device (with automatic tool compensation function)
- (19) Automatic tool tip measuring device
- (20) ATC jib crane  
This is the jib crane for lifting a TUE(S) tool holder.  
Maximum lifting load : 50 kg (110lb)
- (21) Heavy duty type chip conveyor  
Motor : AC 4P, 0.4 kW [0.54 HP]
- (22) Chip Bucket
- (23) Through spindle type coolant function
- (24) Customer specified painting color
- (25) Specification which a table and a live spindle rotate simultaneously (M34-Mode)
- (26) The function which displays the position of crossrail
- (27) Door for tool tip exchange (Splash cover option)
- (28) Specification of hydraulic three-Jaws table



(7) Chip scraper




(28) Specification of hydraulic three-Jaws table



(27) Door for tool tip exchange (Splash cover option)


## Tool holder

Type	L	D	Bite
TA50-ST-160-JU	160(6.29)	-	32×32(1.25×1.25)
TA50-ST-200-JU	200(7.87)	-	32×32(1.25×1.25)
TA50-ST-250-JU	250(9.84)	-	32×32(1.25×1.25)
TA50-BFP-250-JU	250(9.84)	110(4.33)	25×25(0.98×0.98)
TA50-BFP-300-JU	300(11.81)	110(4.33)	25×25(0.98×0.98)
TA50-BFP-350-JU	350(13.77)	110(4.33)	25×25(0.98×0.98)
TA50-BFP-400-JU	400(15.74)	110(4.33)	25×25(0.98×0.98)




Type	L	D	Bite
TA50-ST-160-JU	160(6.29)	-	32×32(1.25×1.25)
TA50-ST-200-JU	200(7.87)	-	32×32(1.25×1.25)
TA50-ST-250-JU	250(9.84)	-	32×32(1.25×1.25)
TA50-BFP-250-JU	250(9.84)	110(4.33)	25×25(0.98×0.98)
TA50-BFP-300-JU	300(11.81)	110(4.33)	25×25(0.98×0.98)
TA50-BFP-350-JU	350(13.77)	110(4.33)	25×25(0.98×0.98)
TA50-BFP-400-JU	400(15.74)	110(4.33)	25×25(0.98×0.98)

Type of tool holders for TUE-(S) series change to "FMX50A-"




### Rigid table construction for more efficient machining

All of the major machine components are constructed of high-grade castings. The table has been provided with ample strength and size. The table is provided with ample strength and size and supported on a large-diameter thrust ball bearing and tapered roller bearing. This construction brings sufficient performance of high speed and heavy machining with extremely high efficiency. In addition, the table is equipped with 4 independent manually-operated jaws and T-slots which guide and hold workpieces in required position so accurately.





- Independent manually-operated jaws  
Four jaws with the following specifications are supplied as standard accessories.
- Maximum clamping force : 4metric tons (8800lbs) (clamping torque 441 N·m [325ft·lbs])
- Weight (one jaw) : 28kg (61.6lbs)



### Maximum machining range

※ Value of TUE-200 in red character. TUE-150 standard in blue character. Common value is written in black character on above drawing.



Minimum boring diameter with ram extended

### Machine Specifications

Machine Specifications	Unit	TUE-150	TUE-200	
Capability and capacity	Table diameter	mm (in)	1450 (57.09) / 2000 (78.74)	
	Maximum swing	mm (in)	2000 (78.74) / 2400 (94.49)	
	Maximum height from table top to ram bottom	mm (in)	1720 (67.72)	
	Maximum cutting height	mm (in)	1550 (61.02)	
	Maximum cutting diameter	mm (in)	2000(78.74)	2400(94.49)
	Maximum cutting force of ram	N (lbf)	24500 (5508)	
	Maximum table load	kg (lbs)	8000 (17600)	15000 (33070)
Travel	Horizontal travel of rail head (X-axis)	mm (in)	-100~1150 (-3.94~45.28)	-50~1350 (-1.97~53.15)
	Vertical travel of ram (Z-axis)	mm (in)	900 (35.43)	
	Vertical travel of cross rail (Not NC axis)	mm (in)	1000 (39.38)	
Table	Table speed	min <sup>-1</sup>	2~400 (Low : 2~100 / High : 8~400)	2~240 (Low : 2~60 / High : 8~240)
	Maximum torque	N·m (ft·lbs)	20930 (15435)	31396 (23153)
Live Spindle [TUE(S)]	Rotation speed	min <sup>-1</sup>	15~3000	
	Maximum torque	N·m (ft·lbs)	233 (171.8)	
Feedrate	Rapid traverse rate of rail head (X-axis)	mm/min (in/min)	15000 (590.55)	
	Rapid traverse rate of ram (Z-axis)	mm/min (in/min)	12000 (472.44)	
	Feedrate (X, Z-axes)	mm/min (in/min)	1~2000 (0.04~78.74)	
	Table index positioning speed (C-axis) [TUE(S)]	deg/min	720	
Ram	Section	mm (in)	250×230 (9.84×9.06)	
Tool	Type of tool shank		7/24 taper JIS 50T and Dia. 145mm flange	
	Type of pullstud		50PU (JIS B 6339-1992) (1-8UNC)	
Motor	Table drive motor (30min/cont.)	kW (HP)	VAC45/37 (60/50)	
	Spindle drive motor (30min/cont.) [TUE(S)]	kW (HP)	VAC18.5/15 (25/20)	
	Feed servo motor	kW (HP)	AC4 (5.4)	
Power source	Electrical power supply		AC200/220V, 50/60Hz	
	Power capacity	kVA	80	
Machine size	Height	mm (in)	5430 (214)	5550 (218)
	Floor area	mm (in)	5100×3750 (200.8×147.6)	5600×4400 (220.5×173.2)
	Machine weight	kg (lbs)	17000 (37480)	21700 (47840)
Accuracy	Positioning (X-axis)	mm (in)	±0.007/500 (±0.0003/20)	
	(Z-axis)	mm (in)	±0.007/500 (±0.0003/20)	
	Positioning repeatability (X, Z-axes)	mm (in)	±0.003 (±0.00012)	
	Positioning (C-axis) [TUE (S)]	arc-sec	±10" per 360 deg.	
Positioning repeatability (C-axis) [TUE (S)]	arc-sec	±5"		

### General view TUE-150(S)

